UL Product iQ™

ZPMV2.E333645 - Wiring, Printed - Component

Wiring, Printed - Component

JIANG XI LEADFLY CIRCUIT CO LTD
A3-4 Xinzhen Industrial Areas,Longnan County
Ganzhou, Jiangxi 341700 China

E333645

Type	Cond Width Min mm(in)	Min Edge mm(in)	Cond Thk mic(mil)	SS/ DS/ DSO	Max Area Diam mm(in)	Assembly Solder Process Temp °C	Solder Process Cycles	Solder Limits °C	Solder Limits sec	Max Oper Temp °C	Flame Class	Meets UL796 DSR	C T I
Multilayer metal base printed wiring boards.													
LD-AL	0.16 (0.006)	0.48 (0.019)	30 (1.18) Int:102	SS	25.4 (1)	-	-	288	60	130	V-0	All	*
Multilayer printed wiring boards													
W-02	0.1 (0.004)	0.2 (0.008)	17 (0.67) Int:35	DS	25.4 (1)	-	-	280	5	130	V-0	All	*
W02	0.075 (0.003)	0.1 (0.004)	17 (0.67) Int:68	DS	50.8 (2)	-	-	288	15	130	V-0	All	*
Single layer metal base printed wiring boards.													
AL88	0.12 (0.005)	0.26 (0.01)	35 (1.38)	SS	76.2 (3)	-	-	288	30	130	V-0	All	0
LD-5	0.18 (0.007)	0.15 (0.006)	17 (0.67)	SS	50.8 (2)	-	-	288	20	130	V-0	All	0
LD-6	0.1 (0.004)	0.1 (0.004)	17 (0.67)	SS	50.8 (2)	-	-	280	20	130	V-0	All	0
LD-7	0.1 (0.004)	0.1 (0.004)	17 (0.67)	SS	50.8 (2)	-	-	288	20	90	V-0	All	0
LD-8	0.13 (0.005)	0.13 (0.005)	17 (0.67)	SS	50.8 (2)	-	-	288	20	130	V-0	All	0
Single layer printed wiring boards													
LD-10	0.15 (0.006)	0.2 (0.008)	17 (0.67)	DS	50.8 (2)	-	-	280	10	130	V-0	All	*
LD-11	0.15 (0.006)	0.2 (0.008)	34 (1.34)	SS	50.8 (2)	-	-	260	10	130	V-0	All	*
LD-W01(ASP 1)	0.08 (0.003)	0.1 (0.004)	17 (0.67)	DS	50.8 (2)	260	3	-	-	130	V-0	All	*

W-01	0.14 (0.006)	0.14 (0.006)	35 (1.38)	DS	50.8 (2)	-	-	260	10	130	V-0	All	*
W01	0.08 (0.003)	0.1 (0.004)	17 (0.67)	DS	50.8 (2)	-	-	288	15	130	V-0	All	*

* - CTI marking is optional and may be marked on the printed wiring board.

(ASP 1) - Assembly Solder process evaluated to IPC-TM-650, 2.6.27 Thermal Stress Assembly Simulation

Marking: Company name or trademark  or file number and type designation. May be followed by a suffix to denote factory identification or flammability classification..

Last Updated on 2022-03-18

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过UL认证，并满足UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明： "© 2022 UL LLC"